


## THE POWER BEHIND POWER







## I□■1000 SPECIFICATION

	CAPACITY	
	VA/W	1000VA/600W
	INPUT	
	Voltage	230VAC
	Voltage Range	140-300VAC
	Frequency	>40 (Auto Sensing)
	OUTPUT	
	Voltage	230VAC
	Voltage Regulation (Batt.Mode)	+/-10%
	Frequency	50Hz
	Frequency Regulation (Batt.Mode)	+/-1 Hz
i	Output Waveform	Modified Sinewave
	BATTERY	
i	Battery Type	12V7Ah x 2pc
i	Backup time at a PC load (120w)	30-35 minutes
	Recharge Time	6 hours to 90% after complete discharge

INDICATOR	NDICATOR	
Normal	Green lighting	
AC Mode	Green lighting	
Battery Mode	Yellow flashing	
Battery Mode	Red lighting	
AUDIBLE ALARM		
Backup Mode	Sounding every 10 seconds	
Low Battery	Sounding every seconds	
Overload	Sounding every 0.5 seconds	
Fault	Continuously sounding	

TRANSFER TIME

PROTECTION	
Full Protection	Discharge, Overcharge and overloa protection
PHYSICAL	
Dimension (mm), DXWXH	350x146x160
WEIGHT	
Net Weight	8.0 kgs
ENVIRONMENT	
Operating Environment	0-40°C
Noise Level	Less than 40dB

Onsite warranty incl. **Battery**