



UPS

THE POWER BEHIND POWER

ICE 600



2 years
Onsite warranty incl.
Battery

ICE600 BACK UP TIME

Monitor

15"

17"

LCD
(watt)



15-20 mins (80w)



13-15 mins (90w)

CRT
(watt)



10-12 mins (120w)



6-8 mins (140w)

CAPACITY

VA/W 600VA/360W

INPUT

Voltage 230VAC

Voltage Range 140-300VAC

Frequency >40 (Auto Sensing)

OUTPUT

Voltage 230VAC

Voltage Regulation (Batt.Mode) +/-10%

Frequency 50Hz

Frequency Regulation (Batt.Mode) +/-1 Hz

Output Waveform Modified Sinewave

BATTERY

Battery Type 12V7Ah x1 pc

Backup time at a PC load (120w) 10-12 minutes

Recharge Time 6 hours to 90% after complete discharge

ICE 600 SPECIFICATION

TRANSFER TIME

Typical 4-8 ms

INDICATOR

AC Mode

Battery Mode Green lighting

AUDIBLE ALARM

Backup Mode Sounding every 10 seconds

Low Battery Sounding every seconds

Overload Sounding every 0.5 seconds

Fault Continuously sounding

PROTECTION

Full Protection Discharge, Overcharge and overload protection

PHYSICAL

Dimension (mm), DXWXH 279X100x142

WEIGHT

Net Weight 4.2 kgs

ENVIRONMENT

Operating Environment 0-40°C, 0-90% relative humidity (non-condensing)

Noise Level Less than 40dB